[11] Patent Number:

4,854,320

[45] Date of Patent:

Aug. 8, 1989

[54]	LASER HEALING METHOD AND
	APPARATUS

[75] Inventors: Douglas K. Dew, Maitland; Long S. Hsu, Orlando; Steven J. Halpern,

Winter Park, all of Fla.

[73] Assignee: Laser Surgery Software, Inc.,

Maitland, Fla.

[21] Appl. No.: 62,861

[22] Filed: Jun. 16, 1987

# Related U.S. Application Data

[63]	Continuation-in-part of Ser. No. 539,527, Oct. 6, 1983
-	Pat. No. 4,672,969.

[51]	Int. Cl.4	A61N 5/00	6
		128/397; 128/303.1	
		219/121.61; 219/121.62; 219/121.70	

## [56] References Cited

#### U.S. PATENT DOCUMENTS

3,467,098	9/1969	Ayres	128/303.1
3,750,670	8/1973	Palanos et al	128/303.1
3,769,963	11/1973	Goldman et al	128/2 R
3,794,040	2/1974	Balamuth	128/303.1
3,865,113	2/1975	Sharon et al	128/303.1
4,122,853	10/1978	Smith	128/303.1
4,266,549	5/1981	Kimura	128/303.1
4,470,414	9/1984	Imagawa et al	128/303.1
4,520,816	6/1985	Schachar et al	. 128/397
4,573,465	3/1986	Sugiyama et al	128/303.1

## FOREIGN PATENT DOCUMENTS

0075860 4/1983 European Pat. Off. .

2809007	2/1978	Fed. Rep. of Germany
3242612	5/1983	Fed. Rep. of Germany
2494986	11/1981	France.
618116	8/1978	U.S.S.R
886907	9/1981	U.S.S.R.

#### OTHER PUBLICATIONS

Jain, Surgery, vol. 85, No. 6, Jun., 1979, "Repair of Small Blood Vessels with the Neodymium-YAG Laser: A Preliminary Report", pp. 684-687.

Jain, The Lancet, Oct. 6, 1984, "Sutureless Extra-Intracranial Anastomosis By Laser", pp. 816-817.

Primary Examiner—Leo P. Picard Attorney, Agent, or Firm—Warren L. Franz

# 57] ABSTRACT

The method and apparatus of the invention use a beam of laser emitted optical energy to effect wound closure and reconstruction of biological tissue. In response to input as to tissue type and thickness, a computer determines the output power, exposure time and spot diameter of the emitted beam to control the application of optical energy to produce thermal heating of biological tissue to a degree suitable for denaturing the tissue proteins such that the collagenous elements of the tissue form a "biological glue" to seal immediately and/or to reconstruct the tissue being heated. In a given embodiment, the computer directly controls output power of the laser by regulating the laser's input current, and limits exposure time by deactivating a shutter mechanism when the determined time is reached. Beam diameter is manually set in response to a displayed value for a sliding scale that controls the working distance between the end of a fiber optic beam guide and the tissue site.

#### 20 Claims, 3 Drawing Sheets

